

Eco US5

48 x 40



Available
with FDA
approval

Universal multi-trip plastic pallet for loads up to 2800lbs (1300kg) in the high rack. The Eco US5 has been engineered as a real all-rounder that offers high performance. It is universally applicable in closed circuits, production plants and goods distribution. The high impact strength of this plastic pallet significantly reduces the risk of damage with such improper handling, and thus extends the service life. The pallet can be equipped with additional metal reinforcements. This makes the pallet highly durable and perfectly suited for high racks. With a net weight starting at only 31 lbs (14 kg), the Eco US5 takes dynamic loads of up to 5600lbs (2500 kg) and racking loads of up to 2800lbs (1250 kg).


Bottom support




> 3 runners (3R)



> 3 runners (3R-M)



> 6 runners (6R)



> 6 runners (6R-M)

Deck options



> open deck (OD)



> closed deck (CD)



Metal reinforcements makes the pallet perfectly suited for high racks.

Technical data*1


| | Bottom support | Top deck | Dimensions [in] / [mm] | Load capacities*2 [lbs] / [kg] | | | Weight [lbs] / [kg] | | |
|--------------------|----------------|--------------------------|------------------------------------|--------------------------------|-----------------|--------------|---------------------|------|---|
| | | | | Static | Dynamic | Racking | PP | ACM | |
| Eco US5 (OD-3R) | 3 runners** | open | 48 x 40 x 6.1 1219 x 1016 x 155 | 8800 4000 | 4400 2000 | 2200 1000 | 31.0 | 14.0 | — |
| Eco US5 (CD-3R) | | closed | | | | | 37.0 | 17.0 | — |
| Eco US5 (OD-6R) | 6 runners | open | | | | | 34.0 | 15.5 | — |
| Eco US5 (CD-6R) | | closed | | | | | 40.0 | 18.0 | — |
| Eco US5 (OD-3R-M)* | 3 runners** | open, metal reinforced | | 11200 5100 | 5600*** 2500 | 2800 1250 | 45.0 | 20.5 | — |
| Eco US5 (CD-3R-M)* | | closed, metal reinforced | | | | | 51.5 | 23.5 | — |
| Eco US5 (OD-6R-M)* | 6 runners | open, metal reinforced | | | | | 48.0 | 21.5 | — |
| Eco US5 (CD-6R-M)* | | closed, metal reinforced | | | | | 54.0 | 24.5 | — |

* 1.0 in coated steel square tube

** only rack in 48 in | 1219 direction

*** only in 48 in / 1219 direction



Entry: 4 ways | Nesting height: - | Safetyrim: 0.2 in / 6 mm (optional without)



nominal sizes in inch | mm

Options

- Color: (other colors on request*3)
- Anti-slip: safety rim, anti-slip on top deck, grommets under deck (12) and under runners (4)
- ESD prevention: —
- > HACCP-compliant PP with FDA approval (freezer additives available)
 - > Individual marking*3
 - > RFID transponders



*1 Figures can vary depending on the raw material used and options applied. *2 Guideline values are based both on experience and parts of test ISO 8611, which tests with evenly distributed loads at room temperature (68°F / 20°C). Varying data may result from different conditions of usage. Your specific requirements can be identified upon request. *3 Minimum quantity required ACM pallets should only be used and stored in a dry environment. We reserve the right to change any of the stated information without prior notice.