

Nest C5.2

45 x 45









>6 runners (6R)



Optional without safety rim



> open deck (OD)



> closed deck (CD)



Rounded edges





Easy handling


Technical data*1

	Previous name	Bottom support	Top deck	Dimensions [in] / [mm]	Load capacities*2 [lbs] / [kg]			Weight[lbs] / [kg]			
					Static	Dynamic	Racking	HD	PE	ACM	
Nest C5.2 (OD-9F)	CPP 440	9 feet, nestable	open	44.9 x 44.9 x 5.5 1140 x 1140 x 140	8800 4000	3300 1500	_	25.5	11.5	27.5	12.5
Nest C5.2 (CD-9F)	CPP 440c		closed					27.5	12.5	30.0	13.5
Nest C5.2 (OD-6R)	CPP 446	6 runners	open	44.9 x 44.9 x 6.4 1140 x 1140 x 163	17600 8000	5300 2400	1300 600	32.0	14.5	36.5	16.5
Nest C5.2 (CD-6R)	CPP 446c		closed					34.0	15.5	38.5	17.5

Entry: 4 ways | Nesting height: 2.4 in / 60 mm | Safetyrim: 0.2 in / 5 mm (optional without)







nominal sizes in inch | mm

Options

Color: ■ (other colors on request*3) > Individual marking*3

Anti-slip: safety rim

ESD prevention: -

^{*}¹ Figures can vary depending on the raw material used and options applied. *² Guideline values are based both on experience and parts of test ISO 8611, which tests with evenly distributed loads at room temperature (68°F / 20°C). Varying data may result from different conditions of usage. Your specific requirements can be identified upon request. *³ Minimum quantity required ACM pallets should only be used and stored in a dry environment. Wereserve the right to change any of the stated information without prior notice.